Topical Practice
IGCSE
PHYSICS
Paper 4

Chapters 13 - 14

EDITION • Volum • STUDENT

CONTENTS

Chapter	Topic	Pages
13	 Electronics and Electric Circuits Circuit Components and Diagrams Analogue and Digital Logic Gates (Cathode-Ray Oscilloscope) 	3 - 20
Atomic Physics Atomic Model The Nucleus, Nuclear Fission and Fusion Radioactivity (Detection, Decay, Half-Life) Alpha, Beta, and Gamma Emissions Safety Precautions 		21 - 39
	CCSF. EXamoull	

Chapter 13: Electronics and Electric Circuits

1 A student is designing a digital electronics circuit and needs to use the logic gate X shown in Fig. 10.1.




Fig. 10.1


(a)	Name the logic gate X.	 [1	1
,	rianno ino logio gato ri.		

(b) Write down the values of the output when the inputs are


(i)	input A low (logic 0), input B low (logic 0),	output
(ii)	input A low (logic 0), input B high (logic 1),	output

- (c) When the student starts to build the circuit, he finds that the store room has run out of this type of logic gate. There is a supply of AND, OR and NOT gates. The student's teacher explains that a combination of two of these gates may be used instead of logic gate X.
 - (i) State the two gates he should use to replace logic gate X.

..... and



[3]
(d) Fig. 10.2 shows a block diagram, not using standard symbols, of a combination of gates.



State the logic levels of points Y and Z when the logic levels of points U and W are both 1.

[Total: 8]

2 Fig. 11.1 shows part of a circuit designed to switch on a security lamp when it gets dark.




Fig. 11.1

When there is a current in the relay coil, switch S closes and the lamp L comes on.

- (a) Write down the name of the component X. (b) The circuit has gaps at A and at B. State the components that need to be connected into these gaps for the circuit to perform its required function. [3] (c) The circuit in Fig. 11.1 is modified. The function of lamp L is now to give a warning when
- the temperature becomes too high.

State any necessary changes of components in the circuit.

[Total: 6]

3 A warning bell is fitted in a photographic dark room. In the dark, the bell is silent but in bright light, it rings. Two circuits linked by a relay R control the bell B. Fig. 10.1 is the circuit diagram for the arrangement.





Fig. 10.1

(a)	(1)	State the name of component 2.
	(ii)	Explain why B rings in bright light.
		[4]
(b)		nange is made to one of the circuits so that B starts to ring when the temperature in room rises.
	Stat	te the change made.
		[1]

[Total: 6]

4 A student carries out an experiment with the circuit shown in Fig. 11.1. The component in the dashed box labelled X is a diode.



- (a) On Fig. 11.1, draw the correct symbol for a diode, connected either way round, in the dashed box labelled X.
 [1]
- (b) (i) +6.0V is applied to point A, 0V to point B.

State what the student observes on the ammeter.

(ii) −6.0V is applied to point A, 0V to point B.

State what the student observes on the ammeter.

[2]

(c) The voltage shown in Fig. 11.2 is applied to the point A of the circuit in Fig. 11.1. Point B is kept at 0V.

On Fig. 11.2, draw a graph of the readings indicated by the voltmeter.





Fig. 11.2

(d) The circuit shown in Fig. 11.3 contains two switches S₁ and S₂ and two indicator lamps L₁ and L₂.




- Name component Z.[1]
- (ii) Complete the table to state whether the lamps are on or off with the switches in the positions stated.

switch S ₁	switch S ₂	lamp L ₁	lamp L ₂
open	closed		\ \·
closed	open		

[2] [Total: 8]

5 Fig. 10.1 is the symbol for a NAND gate with inputs A and B.



(a) Input A and input B can be set to 1 (high) or to 0 (low).

Complete the table below to give the outputs for this NAND gate.

input A	input B	output
0	0	
0	1	
1	0	
1	1	

(b) The two inputs of the NAND gate are joined together and connected to an input C, as shown in Fig. 10.2.




Fig. 10.2


- (i) Determine the output of this NAND gate when
 - input C is set to 0,

input C is set to 1.

(ii) State the name of the logic gate that behaves in the same way as the NAND gate in Fig. 10.2.

(c) A circuit combines three NAND gates.

The inputs to the circuit are P and Q, as shown in Fig. 10.3.



Points R, S and T in the circuit are also labelled.

Input P is set to 0 and input Q is set to 1.

Determine the logic states (0 or 1) of points R, S and T.

6 Fig. 11.1 shows the main components of a cathode-ray oscilloscope.





Fig. 11.1

(a)	(i)	Name the particles that are in the beam.
		[1]
	(ii)	Explain the purpose of the heater.
	(iii)	Explain why there is a vacuum in the tube.
		[1]
(b)		en no potential difference (p.d.) is applied across either the X-plates or the Y-plates, oot is seen in the centre of the fluorescent screen.
		cribe the p.d.s applied to the X-plates and to the Y-plates when the spot moves up down in the centre of the screen.
	X-pl	ates
	Y-pl	ates
		[2]
		[Total: 5]

- **7** An a.c. power supply is connected in series with a metal-filament lamp. A cathode-ray oscilloscope (c.r.o.) is in parallel with the lamp, as shown in Fig. 8.1.
 - Fig. 8.2 is the trace seen on the c.r.o. screen.






Fig. 8.1

Fig. 8.2

A diode is inserted in the circuit, as shown in Fig. 8.3.




Fig. 8.3

Fig. 8.4

- (a) (i) On Fig. 8.4, draw the shape of the trace now seen on the screen.
- [2]

(ii) Suggest a device that uses a diode in this way.

r.	47	
 	11	

(b) State and explain the effect on the lamp of inserting the diode into the circuit.

••••
[2]

[Total: 5]

(a)	(i)	Fig. 10.1 shows t	he symbol for a logi	gate.		
)——		
			Fig. 10	.1		
		Name this logic g	ate.			
	(ii)	Draw the symbol	for a NOR gate.			
						[2]
(b)	(i)	The two inputs of	a NAND gate are b	oth low (logic level	0).	
		Write down the o	utput state.	(1).		
	(ii)	One input of a N level 1).	AND gate is low (lo	gic level 0) and th	ne other input is	high (logic
		Write down the o	utput state.			
						[2]
(c)	A lo	ogic gate contains	a number of compor	nents.		
	Circ	cle one of the follo	wing that is containe	ed in a logic gate.		
		thermistor	transformer	transistor	transmitter	[1]
						[Total: 5]

9 (a) Fig. 10.1 shows an electron beam travelling, in a vacuum, towards the space between a pair of oppositely-charged parallel plates.




Fig. 10.1

On Fig. 10.1, draw carefully the path of the beam between the plates **and** in the space to the right of the plates. [2]

(b) The screen of a cathode-ray oscilloscope (c.r.o.) has a grid of 1 cm squares. Fig. 10.2 shows the trace of an alternating voltage on this screen.




Fig. 10.2

(i) A potential difference of 5.0V across the Y-plates of the oscilloscope moves the spot on the screen a vertical distance of 1.0 cm.

Use Fig. 10.2 to determine the maximum p.d. across the Y-plates.

maximum p.d. =[1]

(ii) The spot on the screen takes 1.0 ms to move 1.0 cm horizontally.

10 (a) Describe the action of

(i) a NOT gate,

(ii) a thermistor.

From Fig. 10.2, determine the time for 1 cycle of the waveform on the screen, and use this time to find the frequency of the alternating voltage.

(b) Fig. 11.1 shows a circuit that switches on a warning lamp when the temperature in an oven falls below a set value.




Fig. 11.1

Explain, with reference to the components in the circuit and point P, why the warning lamp is on when the temperature in the oven is below the set value, (ii) the effect of changing the resistance of R. [Total: 7] 11 A battery charger includes a transformer and a rectifier. Fig. 11.1 represents the transformer, consisting of an iron core with two coils P and Q wound on to the core. coil Q, 2000 turns coil P, 40 000 turns iron core Fig. 11.1 (b) The output of Q is connected to the rectifier circuit. State (i) the name of the circuit component that is used in a rectifier circuit to rectify the a.c. (alternating current),

[Total: 7]

(ii) the property of this component that is used to rectify the current.

12 (a) Fig. 10.1 shows a digital logic circuit, not using the recognised symbols.




Fig. 10.1

Complete the table below to indicate the logic levels of points D and E in the circuit, when points A, B and C are at the logic levels indicated.

0 represents low or off. 1 represents high or on.

Α	В	С	D	Е
0	0	0		8
0	0	1		.0
1	1	1		

[3]

(b) Draw the recognised symbol for an AND gate.

[1]

(c) A NAND gate can be replaced by an AND gate and a NOT gate.

Draw a diagram to show how the AND gate and the NOT gate should be connected. Label clearly the logic gates and any input or output.

[2]

[Total: 6]

13 A charger for a cellphone (mobile phone) is marked:

input: a.c. 240V, 50 Hz, 80 mA. output: d.c. 5.3V, 500 mA.

(a) State

(a)

(i)	the component in the charger that converts a.c. to d.c.,
(ii)	the quantity that has the value 50 Hz.

14 Fig. 11.1 shows the main components of a cathode-ray oscilloscope.




Fig. 11.1

(i)	State the function of component P.	
		.[1]
(ii)	Tick one box to complete the sentence correctly.	
	A cathode-ray oscilloscope contains	
	air at about five times normal atmospheric pressure.	
	air at about normal atmospheric pressure.	
	air at about one fifth of normal atmospheric pressure.	
	a vacuum.	
	neon gas.	[1]
		1,1

[2]

(b) Fig. 11.2 shows the front view of the screen of the cathode-ray oscilloscope.




Fig. 11.2

With no voltage applied between the X-plates or between the Y-plates, the spot is at A.

(i) Place two ticks in each of the blank columns of the table to describe the voltages across the plates when the spot is at points B and C. The column for the spot at A has been completed as an example.

	spot at A	spot at B	spot at C
plate X ₁ at higher voltage than plate X ₂			
plate X ₁ at lower voltage than plate X ₂		,	
no voltage between X-plates			
plate Y ₁ at higher voltage than plate Y ₂			
plate Y ₁ at lower voltage than plate Y ₂			
no voltage between Y-plates	1		

Explain your answers for the spot at point B.	[3]
[1	.[1]
[Total: 6	l: 6]

15 (a) Place **one** tick in each row of the table to indicate one use of a thermistor and one use of a transistor.

	heat detector	light detector	magnetic field detector	rectifier	switch
thermistor					
transistor					

[2]

(b) In Fig. 9.1, lamp A is not glowing brightly.




Fig. 9.1

	Suggest and explain what could be done to component B to ma
	راح المار
[Total: 6]	et o

16 (a) Fig. 9.1 shows the symbol for a logic gate.



Fig. 9.1

(i) State the name of this gate.


(ii) On Fig. 9.1, clearly label an input and an output.

[2]

(b) In the space below, draw the symbol for a fuse.

[1]

(c) Fig. 9.2 shows a circuit.



Component A is not emitting light. It only emits light when the p.d. across it is greater than 1V.

(i) A change to the environment around component B causes component A to emit light.
State the environmental change.

			[1]
ii)	Explain your answer to (i).	MOJILO	
		40	

17 (a) Fig. 10.1 shows the symbol for a logic gate.



Fig. 10.1

(ii) On Fig. 10.1, label an input and an output. [1]

(iii) In the space below, draw the symbol for a NAND gate.

(b) A very low frequency alternating voltage is applied between A and B in the circuit shown in Fig. 10.2.






Fig. 10.2

On each diagram, draw a possible position of the indicator needle of the ammeter at the time in the cycle when


(i) A is positive and B is negative,



(ii) there is no p.d. between A and B,



(iii) A is negative and B is positive.




[3]

[Total: 6]

Chapter 14: Atomic Physics

1 In a research laboratory, a radioactive sample is placed close to a radiation detector. The graph in Fig. 11.1 shows the decay of the sample.



(a)	After 6 days the count rate hardly Explain these observations.	decreases and, in fa	ct, increases a	little at times.
		,0		

(b) Use the graph to determine the half-life of the sample. Explain your working carefully.

		half-life =[4	4
(c)	researcher suggests that a sufficient safet	emitter of α-particles and γ-rays. A junionly precaution, when working with this sample rceps. Explain why this suggestion, althoug	e,
			••

.....[2]

2 (a) Fig. 10.1 shows a wire PQ placed between the poles of a magnet. There is a current in wire PQ.




Fig. 10.1

- (b) The wire PQ in Fig. 10.1 is replaced by a narrow beam of β -particles travelling from left to right.
 - (i) Suggest a suitable detector for the β-particles.

۲1	1	
ь.	4	

(ii) State the direction of the force on the β -particles.

	[1	1
	r.	J

(iii) Describe the path of the β -particles in the space between the poles of the magnet.

111

(iv) State what happens to the air molecules along the path of the β -particles.

[Total: 6]

- 3 The isotope thorium-234 is radioactive. It emits β-particles as it decays.
 - (a) The incomplete nuclide equation represents the decay of thorium-234 to an isotope of protactinium (Pa).

Complete the equation.

$$^{234}_{90}$$
Th \rightarrow Pa + $^{334}_{334}$ Pa (3)

(b) Fig. 11.1 shows a beam of β-particles from a sample of thorium-234 passing into the electric field between two charged plates in a vacuum.





Fig. 11.1

- (i) By drawing on Fig. 11.1, show how the β-particles move as they pass between the plates.
 [1]
- (ii) Explain why the β-particles move in this way.



4 Fig. 9.1 shows an experiment carried out **in a vacuum** to investigate the deflection of α-particles and γ-rays in a magnetic field.



(a) Complete the table to describe the deflection, if any, of the α-particles and the γ-rays in the magnetic field shown. Place one tick in each column.

possible deflection	α-particles	γ-rays
no deflection		
towards N pole of magnet		
towards S pole of magnet		
out of paper		
into paper		

	(D)	THE	experiment of Fig. 9.1 was carried out in a vacuum.	
		Sta	te the effect of carrying out the experiment in air.	
				[2]
	(- \	04-		
	(c)	Sta	te and explain the purpose of the lead cylinder.	
		•••••		[2]
				[Total: 7]
5	(a)	A ra	adioactive source emits α -, β - and γ -radiation.	
		Wh	ich of these radiations	
		•		
		(i)	has the shortest range in air,	
		(ii)	has a negative charge,	
		(iii)	is not deflected in a magnetic field?	
		(,		[2]
	(b)	In a	famous experiment, carried out in a vacuum, a very thin sheet of	f gold was placed in
	(~)		path of alpha particles.	gora mas prassa m
		lt w	as found that a large number of the alpha particles passed thro	ough the sheet with
		little	or no deflection from their original path. A very small number of	
		wer	e reflected back towards the source.	
		(i)	Explain, in terms of the force acting, why the direction of motion	of an alpha particle
			changes when it comes close to the nucleus of a gold atom.	
				[2]

(ii)	State two conclusions, about the nuclei of atoms, that were made from the results of this experiment.
	1
	2
	[2] [Total: 6

- **6** In a laboratory experiment, the isotope uranium-238 is used as a source of α -particles.
 - (a) State
 - (i) one feature of uranium-238 nuclei that is the same for the nuclei of other uranium isotopes,

.....[1]

(ii) one feature of uranium-238 nuclei that is different for the nuclei of other uranium isotopes.

[1]

(b) Fig. 9.1 shows the α -particles from the uranium source being directed at a very thin gold foil, in a vacuum.





Fig. 9.1

			eles, a detector is mo rements are recorded	oved to different positions d.
	Describe the results the structure of atom	_	experiment and exp	lain what they show about
				[4]
7	There are two stable, nat	turally occurring isoto	opes of hydrogen.	[Total: 6]
	Common hydrogen (hydr	, ,		nucleon number of 1.
	Hydrogen-2 (deuterium)	has a nucleon numb	er of 2.	
		ve isotope of hydrog	gen called tritium (hy	drogen-3), with a nucleon
	number of 3.			
	(a) Complete the table f	or neutral atoms of t	hese isotopes.	
	•	hydrogen-1	hydrogen-2 (deuterium)	hydrogen-3 (tritium)
	number of protons			
	number of neutrons			
	number of electrons			[3]
	(b) Two samples of trition	ım are stored in alur	ninium containers of	
	Sample 1 is in a co through the contained		0.5 mm and radiation	n can be detected coming
	Sample 2 is in a cor	tainer of thickness 5	mm and no radiation	comes through.
	(i) State the type of	of radiation coming the	nrough the container	of Sample 1.
				[1]

26

	(ii)	Explain your answer to (b)(i).
		[2]
(c)		der conditions of extremely high temperature and pressure, as in the interior of the n, hydrogen nuclei can join together.
	(i)	Name this process.
		[1]
	(ii)	State whether energy is released, absorbed or neither released nor absorbed during this reaction.
		[1]
(d)		en a nucleus of a certain isotope of uranium is bombarded by a suitable neutron, it ts into two smaller nuclei and energy is released.
	Nar	me this process.
		[1]
		[Total: 9]
(a)	Cor	mplete the following statements.
	(i)	An α -particle consists of
	(ii)	A β-particle consists of
		[3]
(b)	As	α -particles and β -particles pass through a gas, molecules of the gas become ionised.
	Exp	plain what is meant by the ionisation of a gas molecule.
		[1]

(c) Fig. 11.1 shows a beam of α -particles and a beam of β -particles in a vacuum. The beams are about to enter a region in which a very strong magnetic field is acting. The direction of the magnetic field is into the page.




- (i) Suggest why the paths of the particles in the magnetic field are curved.
 - [1]
- (ii) Sketch the paths of both types of particle in the magnetic field.
 - [Total: 8]

[3]

9 In a laboratory at a nuclear power station, a radiation detector is connected to a computer. The readings recorded are displayed on the computer screen.

The detector is switched on. Ten minutes later, at time t = 10 minutes, a small sample of radioactive material is removed from a nuclear reactor and placed near to the detector. Readings are recorded for a further 40 minutes. Fig. 11.1 shows the display.



	(a)	Use	Fig. 11.1 to determ	ine the background count-rate in the laboratory.	
				background count-rate =	[1]
	(b)	Use	Fig. 11.1 to determ	ine the count-rate due to the radioactive sample	
		(i)	at <i>t</i> = 10 minutes,		
				count-rate due to sample =	
		(ii)	at <i>t</i> = 19 minutes.		
				count-rate due to sample =	
					[2]
	(c)	Use	the values obtained	in (b) to estimate the half-life of the radioactive sample.	
				half-life =	[2]
				[Total	
				C	. 0]
10			n-90 is a radioactive nows this decay.	isotope that emits β -particles as it decays. The nuclear equal	ion
			v	$\frac{90}{38}$ Sr $\longrightarrow \frac{a}{b}X + \frac{0}{-1}$ e	
	(a)	Cal	culate		
		(i)	the value of a,		
				a =	
		(ii)	the value of b.		
				b =	
				<i>u</i> –	[2]

(b) (i) Tick the element from the list below that is produced by this decay.

element	proton number	place one tick in this column
selenium	34	
bromine	35	
krypton	36	
rubidium	37	
strontium	38	
yttrium	39	
zirconium	40	
niobium	41	
molybdenum	42	

[1]

(ii) The isotope $\frac{a}{b}X$ is also radioactive and undergoes β -decay.

State the name of the element that is produced by this decay.

E4.1
 [1]

(c) Three nuclei are represented as

83 42X 209 83Y 42Z

State and explain which nuclei are isotopes of the same element.

•••••	

[Total: 6]

11 Fig. 11.1 shows a beam of radiation that contains α -particles, β -particles and γ -rays. The beam enters a very strong electric field between charged plates in a vacuum.

	plate at positive voltage
beam of radiation	
	plate at negative voltage

Fig. 11.1

(a) Indicate the deflection, if any, of the α -particles, β -particles and γ -rays, by placing **one** tick in **each** column of the table.

possible deflection	α-particles	β-particles	γ-rays
no deflection			
towards positive plate		co,	
towards negative plate		<i>, (</i>).	
out of the paper			
into the paper	7		

1]
ני
3]
7]
1

[3]

12 (a) Complete the table below for the three types of radiation.

radiation	nature	charge	stopped by
γ	electromagnetic radiation		
β		negative	
α			thick paper

[3] (b) An isotope of strontium is represented in nuclide notation as ⁹⁰₃₈Sr. For a neutral atom of this isotope, state (i) the proton number, (ii) the nucleon number, (iii) the number of neutrons, (iv) the number of electrons. [3] (c) A sample of a radioactive material is placed near a radiation detector. A count-rate of 4800 counts/s is detected from the sample. After 36 hours the count-rate has fallen to 600 counts/s. Calculate how many more hours must pass for the count-rate to become 150 counts/s. number of hours =[3] [Total: 9] registers a low count rate.

13 A technician sets up a radiation detector in a university laboratory, for use in some experiments. Even before the radioactive source for the experiment is brought into the laboratory, the detector

(a)	Suggest what causes this count rate.
	[1]


(b) A radioactive source that emits α -particles is placed on the laboratory bench and the source is gradually moved closer to the detector.

At first, the detector continues to register a low count rate sometimes slightly less than the count rate registered without the source. The count rate suddenly increases to a very high value when the source is very close to the detector.

Explain these changes in the count rate.	
	[ა

(c) In a second experiment, α-particles pass between two parallel, horizontal metal plates in a vacuum.

They then continue to the detector as shown in Fig. 9.1.



A positive charge is established on the upper plate and a negative charge on the lower plate.

(i) On Fig. 9.1, sketch the new path of the α -particles.

- [2]
- (ii) State what happens to the count rate registered by the detector.

______[1]

[Total: 7]

- 14 (a) An underground water pipe has cracked and water is leaking into the surrounding ground.
 - Fig. 11.1 shows a technician locating the position of the leak.




Fig. 11.1

A radioactive isotope is introduced into the water supply and the water that leaks from the crack is radioactive.

The technician tries to locate an area above the pipe where the radioactive count rate is higher than in the surrounding area.

(i)	State and explain the type of radiation that must be emitted by the isotope for the leak be detected.	
		.[2]
(ii)	The half-life of the isotope used is 6.0 hours.	
	Explain why an isotope with this half-life is suitable.	
	<u> </u>	
		- []

(b) Caesium-133 is a stable isotope of the element caesium, but caesium-135 is radioactive.

A nucleus of caesium-133 contains 78 neutrons and a nucleus of caesium-135 contains 80 neutrons.

Put **one** tick in each row of the table to indicate how the number of particles in a neutral atom of caesium-133 compares with the number of particles in a neutral atom of caesium-135.

The first row has been completed already.

	particles in caesium-133							
	2 more than caesium-135	1 more than caesium-135	equal to caesium-135	1 fewer than caesium-135	2 fewer than caesium-135			
number of neutrons					1			
number of protons								
number of nucleons								
number of electrons								

[2]

15	(a)	State the nature of an α -particle.
	(b)	Describe how an electric field between two charged plates could be used to determine whether a beam of particles consists of α - or β -particles.
		[2]
	(c)	Describe the path of γ-rays in a magnetic field.
	(d)	State what is meant by the term <i>isotopes</i> . Use the terms proton number and nucleon number in your explanation.
		[3]
		[Total: 7]
16	(a)	State the nature of γ-rays
	(b)	A beam of α -particles and β -particles passes, in a vacuum, between the poles of a strong magnet.
		Compare the deflections of the paths of the two types of particle.

	(c)		eam of β -particles passes, in a vacuum, through the electric field between a pair of ositely charged metal plates.
		Des	scribe the path of the particles.
			[2]
	(d)	The	nuclear equation shows the decay of an isotope of polonium.
			${}_{Z}^{A}Po \rightarrow {}_{82}^{206}Pb + {}_{2}^{4}X$
		(i)	State the nature of X.
			[1]
		(ii)	Calculate the values of A and Z.
			A = Z =[1]
			[Total: 7]
7	Ura	nium	n-238 and uranium-234 are radioactive isotopes of the element uranium.
			m-238 nucleus is different from a uranium-234 nucleus but both decay by the emission of rticle.
	(a)	(i)	In terms of the particles in each, state how a nucleus of uranium-238 differs from a nucleus of uranium-234.
		(ii)	Although the two nuclei are different, they are both nuclei of uranium.
		(11)	State a property that makes these isotopes the same element.
			otate a property that makes these isotopes the same dement.
			[1]
	(b)	Wh	en α -particles pass through air, they are more strongly ionising than β -particles.
		Sug	ggest two reasons why this is so.
			[2]

(c) In an experiment, α -particles are allowed to strike a thin gold foil in a vacuum.

Almost all the α-particles pass straight through the gold undeflected. Only a very small number of α -particles are deflected from their original path.

This result reveals certain features of the atoms of the gold.

State what is shown about atoms by the fact that

(i)	most α-particles	pass	straight	through	the	gold	undeflected.
\-/						3	,

(ii) some α-particles are deflected back the way they came.

[Total: 7]

18 (a) The counter of a radiation detector placed close to a radioactive source gives a count rate of 1600 counts/s. The half-life of the source is 1 week.

Ignoring background radiation, calculate the count rate

(i) 1 week after the first measurement,

count rate =[1]

(ii) 3 weeks after the first measurement.

count rate =[1]

(b) Fig. 11.1 shows the arrangement for an experiment to investigate the shielding of radioactive sources.




Fig. 11.1 (not to scale)

Samples containing three different radioactive sources are placed, one at a time, in the position shown.

Ē

The table shows the count rates when a radiation detector is placed at the positions A to E.

Complete the table to indicate whether α -particles, β -particles or γ -rays are emitted from each sample.

	Α	В	С	D	E	type of radiation emitted
sample 1	high	high	high	high	low	
sample 2	high	high	low	0	0	
sample 3	high	0	0	0	0	

(c) State which type of radiation, α , β or γ , is the most strongly ionising.

.....[1] [Total: 6]

19 (a) State, in terms of the particles in each nucleus, how the nuclei of two isotopes of the same element are different.

.....[1]

(b) Fig. 11.1 shows a graph of nucleon number against proton number. The nucleus ²¹²₈₃Bi is plotted on the graph at the cross marked P.




Fig. 11.1

- (i) On Fig. 11.1,
 - 1. plot a cross labelled Q for the nucleus formed when the $^{212}_{83} \rm Bi$ nucleus emits an α -particle,
 - 2. plot a cross labelled R for the nucleus formed when the $^{212}_{83}$ Bi nucleus emits a β -particle.

[4]

[3]

(ii) The half-life for the decay of $^{212}_{83}$ Bi is 60 minutes.

A sample of $^{212}_{83}$ Bi is placed at a fixed distance from a detector. The initial measurement of the count rate from the sample of $^{212}_{83}$ Bi is 2400 counts per minute.

Calculate the count rate from the sample 5.0 hours later.

count-rate =[2]

[Total: 7]